

CLAIMS

What is claimed is:

1. A method of providing flexible protection in a computer system by decoupling protection from privilege, the method comprising:
 - enabling receipt of information describing two or more types of protection;
 - enabling receipt of information describing a relationship between said two or more types of protection and portions of code that are executed in a same privilege level of the computer system, wherein said relationship is not required to be linear; and
 - enabling the association of said information describing said two or more types of protection and said information describing said relationship with said portions of code.
2. The method of Claim 1, wherein said relationship is user definable.
3. The method of Claim 1, wherein said portions of code are domains and each of said types of protection is defined at least in part by one or more domain attributes.
4. The method of Claim 3, wherein said one or more domain attributes includes a domain identifier that specifies to a unique value for a particular domain.
5. The method of Claim 3, wherein said one or more domain attributes includes a Private Key that specifies a unique value for protecting each user that concurrently uses a particular domain.
6. The method of Claim 3, wherein said one or more domain attributes includes a SharedCode Key that specifies a value that a particular domain must use to access code associated with another domain.
7. The method of Claim 3, wherein said one or more domain attributes includes a SharedData Key that specifies a value that a particular domain must use to access data associated with another domain.
8. The method of Claim 3, wherein said one or more domain attributes includes an AllowOthers that specifies a value that a particular domain must use to access code associated with another domain in conjunction with said particular domain performing cross-domain switching to said other domain.

9. The method of Claim 3, wherein said one or more domain attributes includes an AccessOthers Key that specifies a value that is used to request access of code associated with a particular domain on behalf of another domain.

10. A method of providing flexible protection in a computer system by decoupling protection from privilege, the method comprising:

- detecting a request from a first portion of code to access a second portion of code, wherein said first and second portions of code are executed in a same privilege level of said computer system;

- determining whether said first portion of code is allowed to access said second portion of code based on information describing two or more types of protection and also based on information describing a relationship between said two or more types of protection and said portions of code, wherein said relationship is not required to be linear; and

- if said relationship specifies that said first portion of code may access said second portion of code, then

- allowing said first portion of code to access said second portion of code;

- else

- not allowing said first portion of code to access said second portion of code.

11. The method of Claim 10, wherein said information describing said two or more types of protection and said information describing said relationships are associated with said portions of code and wherein the method further comprises retrieving said information describing said two or more types of protection and said information describing said relationships .

12. A computer system comprising:

- a memory unit; and

- a processor coupled to the memory unit, the processor for executing a method for enforcing protection in a computer system by decoupling protection from privilege, the method comprising:

- enabling at a user interface receipt of information describing two or more types of protection;

- enabling at the user interface receipt of information describing a relationship between said two or more types of protection and portions of code are executed

in a same privilege level of the computer system, wherein said relationship is not required to be linear; and

enabling at a link-editor the association of said information describing said two or more types of protection and said information describing said relationship with said portions of code.

13. The computer system of Claim 12, wherein said relationship is user definable.

14. The computer system of Claim 12, wherein said portions of code are domains and each of said types of protection is defined at least in part by one or more domain attributes.

15. A computer system comprising:

a memory unit; and

a processor coupled to the memory unit, the processor for executing a method for providing flexible protection in a computer system by decoupling protection from privilege, the method comprising:

detecting at a memory manager a request from a first portion of code to access a second portion of code, wherein said first and second portions of code are executed in a same privilege level of said computer system;

determining at said memory manager whether said first portion of code is allowed to access said second portion of code based on information describing two or more types of protection and also based on information describing a relationship between said two or more types of protection and said portions of code, wherein said relationship is not required to be linear; and

if said relationship specifies that said first portion of code may access said second portion of code, then

allowing at said memory manager said first portion of code to access said second portion of code;

else

not allowing at said memory manager said first portion of code to access said second portion of code.

16. The computer system of Claim 15, wherein said information describing said two or more types of protection and said information describing said relationships are associated with said portions of code and wherein the method further comprises retrieving at a loader said information describing said two or more types of protection and said information describing said relationships .

17. A computer-usable medium having computer-readable program code embodied therein for causing a computer system to perform a method of providing flexible protection in a computer system by decoupling protection from privilege, the method comprising:

enabling receipt of information describing two or more types of protection;

enabling receipt of information describing a relationship between said two or more types of protection and portions of code that are executed in a same privilege level of the computer system, wherein said relationship is not required to be linear; and

enabling the association of said information describing said two or more types of protection and said information describing said relationship with said portions of code.

18. The computer-usable medium of Claim 17, wherein said relationship is user definable.

19. The computer-usable medium of Claim 17, wherein said portions of code are domains and each of said types of protection is defined at least in part by one or more domain attributes.

20. The computer-usable medium of Claim 19, wherein said one or more domain attributes includes a domain identifier that specifies to a unique value for a particular domain.

21. The computer-usable medium of Claim 19, wherein said one or more domain attributes includes a Private Key that specifies a unique value for protecting each user that concurrently uses a particular domain.

28. The computer-usable medium of Claim 19, wherein said one or more domain attributes includes a SharedCode Key that specifies a value that a particular domain must use to access code associated with another domain.

29. The computer-usable medium of Claim 19, wherein said one or more domain attributes includes a SharedData Key that specifies a value that a particular domain must use to access data associated with another domain.

22. The computer-usable medium of Claim 19, wherein said one or more domain attributes includes an AllowOthers that specifies a value that a

particular domain must use to access code associated with another domain in conjunction with said particular domain performing cross-domain switching to said other domain.

23. The computer-usable medium of Claim 19, wherein said one or more domain attributes includes an AccessOthers Key that specifies a value that is used to request access of code associated with a particular domain on behalf of another domain.